



- TECHICAL REQUIREMENTS
1. CANTILEVER STRENGTH: 2500# [11.3KN]
 2. TENSILE STRENGTH: 5000# [22.7KN]
 3. TORSION STRENGTH: 6000"#[27.2KN.M]
 4. COMPRESSION STRENGTH: 30000# [136KN]
 5. NEMA VOLTAGE RATING: 13.2KV
 6. 50 HERTZ WITHSTAND-DRY: 38KV
 7. 50 HERTZ WITHSTAND-DEW: 28KV
 8. IMPULSE WITHSTAND: 95KV
 9. GLAZE: ANSI 70 LIGHT GREY
 10. APPLICABLE STANDARD: ANSI C29.10-1989



EGER PRODUCTS, INC.

REVISIONS:

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 EGER PRODUCTS, INC.. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
 EGER PRODUCTS INC. IS
 PROHIBITED.

DATE: 8/1/2014

CUSTOMER:

SCALE: NTS

A30-3

DRAWN BY: E. GREEN

DWG. INDOOR BUS SUPPORT

APPROVED BY:

MATERIAL: