



TECHICAL REIUREMENTS

1. CANTILEVER STRENGTH: 2000# [9.1KN]
2. TENSILE STRENGTH: 5000# [22.7KN]
3. TORSION STRENGTH: 6000" [27.2KN.M]
4. COMPRESSION STRENGTH: 30000# [136KN]
5. NEMA VOLTAGE RATING: 14.4KV
6. 50 HERTZ WITHSTAND-DRY: 50KV
7. 50 HERTZ WITHSTAND-DEW: 30KV
8. IMPULSE WITHSTAND: 110KV
9. GLAZE: ANSI 70 LIGHT GREY
10. APPLICABLE STANDARD: ANSI C29.10-1989



EGER PRODUCTS, INC.

REVISIONS:

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
EGER PRODUCTS, INC.. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
EGER PRODUCTS INC. IS  
PROHIBITED.

DATE: 8/1/2014

CUSTOMER:

SCALE: NTS

A30-4

DRAWN BY: E. GREEN

DWG. INDOOR BUS SUPPORT

APPROVED BY:

MATERIAL: